Accessories voltage tester up to 1000 V

	Art. No.	Type	Description	SPB all types	ZAP all types	DSP 4 / DSP 4F	DSP 4ST /DSP 4UL / DSP 5	DSP thread set required	LSP 4B / LSP 4L
Extensions	81020	SPB-S500-Y*	Extension 515 mm insulated stainless steel tube, 1000 V 515 x 20 x 20 mm; 0,070 kg	■	■				
	81022	SPB-S600-Y*	Extension 615 mm insulated stainless steel tube, 1000 V 615 x 20 x 20 mm; 0,080 kg	■	■				
	81028	SPB-S820-Y*	Extension 820 mm light GRP-tube, 1000 V 820 x 20 x 20 mm; 0,115 kg	■	■				
	84313	LSP-S500-Y*	Extension 505 mm attachable insulated stainless steel tube, 1000 V 505 x 20 x 20 mm; 0,075 kg			■			■
	84010	DSP-S550-Y*	Extension 550 mm screwable insulated stainless steel tube, 1000 V 550 x 30 x 30 mm; 0,090 kg			■	■	■	
	84014	DSP-S850-Y*	Extension 850 mm screwable light GRP-tube, 1000 V 860 x 30 x 30 mm; 0,090 kg			■	■	■	
	81031	S-HUELSE	Plastic sleeve for storage of extensions up to 600 mm Suitable for a pair of extensions 350 x 45 x 45 mm; 0,070 kg						

* Please select the electrode shape when ordering
- Electrode Y for overhead lines (standard)
- Electrode i for busbars and measuring points

Insertion prod	81021	SPB-S20-A	Insertion prod 20 mm screwable for tests on underground cables, 1000 V 90 x 20 x 20 mm; 0,015 kg	■	■				
	84321	DSP-S20-A	Insertion prod 20 mm screwable for tests on underground cables, 1000 V 140 x 30 x 30 mm; 0,040 kg			■	■	■	
Pin prod	81023	SPB-S65	Flexible pin prod 3 x 65 mm screwable for narrow test points CAT IV 600 V / CAT III 1000 V 145 x 20 x 20 mm; 0,015 kg	■	■				
	84013	DSP-S57	Flexible pin prod 3 x 57 mm attachable for narrow test points CAT IV 600 V / CAT III 1000 V 145 x 20 x 20 mm; 0,015 kg			■			■
	84315	DSP-S56	Flexible pin prod 3 x 56 mm screwable for narrow test points CAT IV 600 V / CAT III 1000 V 180 x 30 x 30 mm; 0,040 kg			■	■	■	
	84318	DSP-S110	Flexible pin prod 3 x 110 mm screwable for narrow test points CAT IV 600 V / CAT III 1000 V 235 x 30 x 30 mm; 0,040 kg			■	■	■	

The dimensions and weights include the product packaging

Accessories voltage tester up to 1000 V

	Art. No.	Type	Description	SPB all types	ZAP all types	DSP 4 / DSP 4F	DSP 4ST /DSP 4UL / DSP 5	DSP thread set required	LSP 4B / LSP 4L
Adapter	81029	SPB-S-ADA	Screwable adapter with 4 mm socket suitable for the connection of test leads CAT IV 600 V / CAT III 1000 V 70 x 20 x 20 mm; 0,015 kg	■	■				
	84011	DSP-S-ADA	Attachable adapter with 4 mm socket suitable for the connection of test leads CAT IV 600 V / CAT III 1000 V 70 x 20 x 20 mm; 0,015 kg			■			■
	84312	DSP-S-ADAS	Screwable adapter with 4 mm socket suitable for the connection of test leads CAT IV 600 V / CAT III 1000 V 120 x 30 x 30 mm; 0,035 kg			■	■	■	
DSP thread set	84019	DSP -G4	Thread set including glue for DSP 4 / DSP 4F Required for the use of screw-on extensions and adapters 170 x 100 x 30 mm; 0,020 kg						
	84023	DSP ST-G4	Thread set including glue for DSP 4ST / DSP 4FST / DSP 4UL Required for the use of screw-on extensions and adapters 170 x 100 x 30 mm; 0,020 kg						
	84024	DSP -G5	Thread set including glue for DSP 5 / DSP 5B / DSP 5ST Required for the use of screw-on extensions and adapters 170 x 100 x 30 mm; 0,020 kg						
Test lines	84311	L-SETR	Test line 1 m with two 4 mm plugs, red including crocodile clip, opening width 20 mm CAT IV 600 V / CAT III 1000 V 170 x 100 x 30 mm; 0,060 kg	■	■	■	■		■
	84314	L-SETS	Test line 1 m with two 4 mm plugs, black including crocodile clip, opening width 20 mm CAT IV 600 V / CAT III 1000 V 170 x 100 x 30 mm; 0,060 kg	■	■	■	■		■
Testbox	81041	SP 200	Manageable voltage source testbox for enhanced self-test generates 50 - 690 V test voltage incl. 6 AA batteries, Not suitable for testing with screwed-on extension probes. 170 x 75 x 75 mm; 0,380 kg	■	■	■	■		■
Protective cap	24315	SPB-CAP	Protective cap for Prüfball SPB / ZAP for adjusting the electrode length 4/15 mm and as transport protection Price for packaging = 2 pieces 170 x 100 x 30 mm; 0,060 kg	■	■				